

## RELATED STANDARDS

### Common Codes

~~A decision made in 1993 by a FERC established standards development group (EBB Working Group 5) resulted in a location coding system which cross references proprietary point codes to a common industry supported location code. This common location code, called the GRID Code, was developed based on the American Petroleum Institute (API) well code model. The FERC, in Order 563-A, directed the industry to establish any necessary relationships and to proceed with the implementation of the GRID Code. To achieve this implementation, in August 1994 trade associations representing three segments of the natural gas industry entered into an agreement with Petroleum Information Corporation (PI) to develop and maintain the PI *GRID*™ Common Code database. As GISB prepared standards for capacity release (July 1995) and nominations (September 1995), GISB fully endorsed the use of the PI *GRID*™ common codes.~~

~~However, after extensive consideration by GISB's Common Code Subcommittee, GISB adopted, on September 30, 1996, a new Common Code for Gas Transaction Points, the NAESB WGQ/PI Data Reference Number (generally referred to as "DRN"). The DRN is a one to nine digit, non intelligent number also assigned by IHS (successor to PI), which has a one to one relationship with the PI *GRID*™ Code. For more information, access the NAESB Web Page at [www.naesb.org](http://www.naesb.org).~~

In keeping with the trends in other industries involved with EDI, ~~EBB Working Group REQ TEIS recommended recommends~~ the acceptance of the D-U-N-S®<sup>1</sup> Number as a common company identifier. ~~This recommendation was also adopted in FERC Order 563-A.~~ The D-U-N-S® Number is assigned to companies by the Dun & Bradstreet Corporation (D&B). Similarly, ~~as GISB NAESB prepared standards for capacity release (July 1995) and nominations (September 1995), GISB fully endorsed the use of the D-U-N-S® Number common code.~~

For NAESB ~~WGQ-REQ~~ Common Code purposes, an entity will use one and only one D-U-N-S® Number. Entity common codes should be "legal entities," that is, Ultimate Location, Headquarters Location, and/or Single Location (in Dun & Bradstreet Corporation ("D&B") terms). However, in the following situations, a Branch Location (in D&B terms) can also be an entity common code: 1. When the contracting party provides a D-U-N-S® Number at the Branch Location level; or 2. to accommodate accounting for an entity that is identified at the Branch Location level. Since D&B offers customers the option of carrying more than one D-U-N-S® Number per entity, please refer to NAESB's Web Page at [www.naesb.org](http://www.naesb.org) for directions on determining the one and only one D-U-N-S® Number constituting the NAESB ~~WGQ-REQ~~ Entity Common Code.

~~In the datasets, an asterisk by a data element means that it is a "common code," so the field will reflect the industry supported common code for location or company.~~

### NAESB WGQ Electronic Data Interchange Trading Partner Agreement

~~In 1998, GISB adopted Standard 6.3.3, the NAESB WGQ Electronic Data Interchange Trading Partner Agreement (TPA) for exchange of data within the gas industry. The NAESB WGQ TPA defines the relationship of the sender and receiver of NAESB WGQ Standard ASC X12~~

<sup>1</sup> D-U-N-S® is a registered trademark of Dun & Bradstreet, Inc.

~~documents. This agreement represents a complete set of balanced terms which a company should accept whether it is sender or receiver of electronic documents. It has established all the data items necessary to exchange electronic documents in a step by step, fill in the blank model form. The use of the TPA minimizes preparation, negotiation and review time. This will allow more time for implementation of electronic commerce. Copies of this agreement may be obtained from the NAESB office or may be downloaded from the NAESB home page at [www.naesb.org](http://www.naesb.org).~~

## Party Roles

~~In all of the transaction sets, there are multiple parties that may be involved in the transaction. There are utilities, marketers, government entities, and various service providers. The Utilities and Marketers are self explanatory. The government entities may be a state commission such as ERCOT in Texas. The service providers can be a CIS provider and/or EDI/EDM provider. There are the Transportation Service Provider (a.k.a. Pipeline or Transporter), the Service Requester (a.k.a. Shipper), Service Requester Agent (a.k.a. Shipper's Agent) and Third Party Service Provider (a.k.a. Third Party Agent). It is important to distinguish between the role of the Service Requester Agent and the Third Party Service Provider.~~

~~The service providers normally will not be identified in the envelope or body of the transaction. The utility, marketer, and government entity will be Identified both in the envelope, or ISA/GS segments and the body of the transaction in the N1 name segments.~~

~~The Service Requester Agent is the party contractually authorized by the Service Requester to submit business transactions to the Transportation Service Provider on behalf of the Service Requester for a service requester contract. Once the Service Requester Agent is contractually authorized, the agent becomes the Service Requester for subsequent business transactions unless and until the agency relationship is terminated.~~

~~The Third Party Service Provider is the communications agent that the Service Requester or Service Requester Agent may subscribe to in order to send and receive transactions with the Transportation Service Provider.~~

~~It is possible that a single entity may, at times, provide the role of a Service Requester Agent for one party while providing the role of Third Party Service Provider for another party. Likewise, a single entity could be both Service Requester Agent and Third Party Service Provider for a single party.~~

~~In EDI implementation, the party that is authorized to send and receive transactions will be the party identified in the transmission envelope (ISA Header Segment). If the sending party is a Service Requester, Service Requester Agent or Third Party Service Provider, their appropriate identifiers will appear here. In all cases, the Transportation Service Provider, Service Requester and Service Requester Agent (if applicable) will be identified in the body of the transaction (N1 Name Segment).~~

## ANSI ASC X12 Standards

~~The NAESB WGQ-REQ standards reflect an industry utilization of the American National Standards Institute (ANSI) ASC X12 standards maintained by the Data Interchange Standards Association, Inc. (DISA). The technical implementation documents included in this manual reflect the NAESB WGQ~~

[REQ](#) subset of the ANSI ASC X12 standards versions. It is recommended that any industry participant who wishes to utilize the ANSI ASC X12 standards should also have a copy of the ANSI ASC X12 Standards Reference document for a full understanding of the X12 requirements. NAESB members may purchase an ANSI reference document through NAESB by contacting the NAESB office. Non-NAESB industry participants may purchase the reference document by contacting:

Manager of Publications  
DISA  
333 John Carlyle Street, Suite 600  
Alexandria, VA 22314  
Voice: 703-548-7005  
Fax: 703-548-5738  
[www.disa.org](http://www.disa.org)

As a member of ANSI, NAESB [WGQ-REQ](#) will utilize the ANSI ASC X12 standards and remain in full compliance. In all standards, occasions arise where the standard does not fully meet a need. NAESB [WGQ-REQ](#) recognizes this and will add interim usages and code values when required. When NAESB [WGQ-REQ](#) utilizes an interim solution, NAESB [WGQ-REQ](#) will apply to ANSI and the appropriate ANSI organizations for acceptance of the interim solution. ANSI's final solution may provide a usage or code value different than the interim solution. NAESB [WGQ-REQ](#) standards will be updated to reflect the final solution.

The architecture of ASC X12 is designed for end to end communications. The translator that generates the ASC X12 file and envelope will assign control numbers and counts that will appear within the ISA/IEA segments of the transaction and within the GS/GE segments of the transaction. These numbers and counts allow the translator to ensure that all of the segments in an envelope and all of the data elements in an envelope have been received and that the transmission was complete.

### ISA contents

The ISA segment marks the beginning of an X12 document. It can be equated to an envelope that a paper document would come in via the mail. The envelope may contain one or more functional groups (defined by the GS segment) and one or more transaction sets.

The ISA is the interchange control segment to be utilized on all NAESB [WGQ-REQ](#) X12 standards. The segment identifies the sender and receiver of the document. The Interchange Sender ID/Interchange Receiver ID is published by both the sender and receiver for other parties to use as the sender/receiver ID to route data to them. The sender must always code the sender's ID in the sender element and the designated receiver's ID in the receiver ID. Trading partners utilizing a password for their documents will use the Security Information element. The receiver of the document identifies a password for the sender to include in this element. [This sender and receiver information is specified in the NAESB \[WGQ-REQ\]\(#\) Electronic Data Interchange Trading Partner Agreement.](#)

There are additional elements in the ISA segment. These elements are traditionally assigned by the sending party's translator. These elements inform the receiver of the date/time that the envelope was generated, the X12 version number being utilized, whether the transmission is for test or production purposes, and what characters were used to designate the end of a sub element, element or segment. Different characters must be chosen for the sub element, element and segment delimiters. These delimiting characters must never appear in the data.

For more information on the ISA segment and the possible values for its elements, contact DISA at the above address or consult the appropriate version of the ANSI ASC X12 Standards Reference document corresponding to the NAESB [WGQ-REQ](#) transaction set being sent/received. Information about control segments (including the ISA and IEA) can be found in the Overview/Introduction and Control Standards sections of the reference document. Specific information about the ISA and IEA segments and corresponding elements can be found in the Segment Directory and Data Element Dictionary sections.

### GS contents

The GS segment indicates the beginning of a functional group and provides control information for the data that follows it. A functional group can be defined as a group of transactions related to one business application. Within a mailing envelope, there may be a bundle of information relating to imbalances and a bundle of information relating to measurement information. Each of these 'bundles' is sent within its own (or a separate) GS Functional Group Header and a GE Functional Group Trailer in the X12 environment. The sender of a transmission provides the Application Sender's Code that the receiver of the transmission will reflect back on acknowledging documents. The receiver of a transmission provides the Application Receiver's Code that the sender will include in the transmission for the receiver to utilize in routing to internal applications. Group Control Numbers are originated and maintained by the sender of the document.

For more information on the GS segment and the possible values for its elements, contact DISA at the above address or consult the appropriate version of the ANSI ASC X12 Standards Reference document corresponding to the NAESB [WGQ-REQ](#) transaction set being sent/received. Information about control segments (including the GS and GE) can be found in the Overview/Introduction and Control Standards sections of the reference document. Specific information about the GS and GE segments and corresponding elements can be found in the Segment Directory and Data Element Dictionary sections.

### 997 Usage

The 997 Functional Acknowledgment is used to indicate the results of the syntactical analysis of the X12 documents. The documents include the transaction sets and functional groups with an ISA/IEA envelope. This standard covers all of the X12 and NAESB [WGQ-REQ](#) standard criteria that the receiver of the document has incorporated into the receiver's translator. The translator may be set to accept all information into the receiver's application processing, it may be set to accept only ANSI ASC X12 compliant information into the receiver's application processing, or it may be set to accept only ANSI ASC X12 and NAESB [WGQ-REQ](#) compliant information into the receiver's application processing. Compliance checking, in a translator, may be set to any of several levels. NAESB [WGQ-REQ](#) recommends that compliance checking be set to the element level in the Functional Acknowledgment.

The 997 informs the originator of the transaction whether the translator accepted the file, accepted it with errors, or rejected it. When errors occur, the 997 identifies the location and type of error that was encountered. Once a transaction passes the translator, the 997 is sent to the originator of the transaction and the data (if accepted) is passed on to the receiver's business application for processing.

### **Hypertext Transfer Protocol (HTTP)**

The Hypertext Transfer Protocol (HTTP) is an application-level protocol with the lightness and speed necessary for distributed, collaborative, hypermedia information systems. It is a generic, stateless, object-oriented protocol which can be used for many tasks, such as name servers and distributed object

management systems, through extension of its request methods (commands). A feature of HTTP is the typing of data representation, allowing systems to be built independently of the data being transferred.

HTTP has been in use by the World-Wide Web global information initiative since 1990. Appendix A of the Electronic Delivery Mechanism Related Standards manual contains a listing of the HTTP version(s) supported by NAESB [WGQREQ](#).

HTTP transaction-set Code Values

The following table contains a list of code values to be used with the transaction-set data element, which is a mutually agreeable (MA) data element in the HTTP Request.

HTTP transaction-set Code Values	NAESB WGQ Standard Number	Transaction Set Description
G873NMST	1.4.1	Nomination
G874NMQR	1.4.2	Nomination Quick Response
G873RQCF	1.4.3	Request for Confirmation
G873RRFC	1.4.4	Confirmation Response
G873SQTS	1.4.5	Scheduled Quantity
G873SQOP	1.4.6	Scheduled Quantity for Operator
G874CRQR	1.4.7	Confirmation Response Quick Response
G860PDAL	2.4.1	Pre-determined Allocation
G865PDQR	2.4.2	Pre-determined Allocation – Quick Response
G865ALLC	2.4.3	Allocation
G811IMBL	2.4.4	Shipper Imbalance
G867MSIN	2.4.5	Measurement Information
G867MAUS	2.4.6	Measured Volume Audit Statement
G814RQIN	2.4.7	Request for Information
G814RRIN	2.4.8	Response to Request for Information
G811TSIN	3.4.1	Transportation/Sales Invoice
G820PYRM	3.4.2	Payment Remittance
G822STAC	3.4.3	Statement of Account
G811SRCA	3.4.4	Service Requester Level Charge/Allowance Invoice
G840CROF	5.4.1	Offer Download
G843CRBR	5.4.2	Bid Download
G843CRAN	5.4.3	Award Download
G832CRRC	5.4.4	Replacement Capacity
G843CRWD	5.4.5	Withdrawal Download
G840UPWD	5.4.6	Withdrawal Upload
G840UDOF	5.4.7	Offer Upload

NAESB WGQ Electronic Delivery Mechanism Related Standards

HTTP transaction-set Code Values	NAESB-WGQ Standard Number	Transaction Set Description
G843UDVL	5.4.8	Offer Upload Quick Response
G840UDRC	5.4.9	Offer Upload Notification
G843UDBC	5.4.10	Offer Upload Bidder Confirmation
G824UDCV	5.4.11	Offer Upload Bidder Confirmation Quick Response
G567UDFD	5.4.12	Offer Upload Final Disposition
G840QAUC	5.4.13	Operationally Available and Unsubscribed Capacity
G846UPRD	5.4.14	Upload of Request for Download of Posted Datasets
G846RURD	5.4.15	Response to Upload of Request for Download of Posted Datasets
G864SWNT	5.4.16	System-Wide Notices
G864CRNS	5.4.17	Note/Special Instruction
G843BDUP	5.4.18	Bid Upload
G843BDQR	5.4.19	Bid Upload Quick Response
G997FNAK	N/A	Functional Acknowledgement