

# ANSI Compliant Nomination Quick Response and Confirmation Response Quick Response Working Document

Discussed at the following meetings:

01/12/2000

mapped to ASC X12 874; used version 4032 as a base X12 standard

GISB Nomination Quick Response (1.4.2)

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
----------	---------	---------	------------------------	--	---	----------------	-----------------

Heading:							
0100	ST		M/1				
0200	BGN		M/1				
		BGN01 - 353	M	27 - Verify		ID	2/2
		BGN02 - 127	M	assigned identifier	The PDA number assigned by the PDA originator in the BGN02.	AN	1/22 *
		BGN03 - 373	M	date	The PDA issue date.	DT	8/8
		BGN07 - 640	O	V4 - PDA Quick Response	mark as must use	ID	2/2
		BGN08 - 306	O	EZ - Exception Occurred RZ - Reject - Header Level Errors WQ - Accept	mark as must use	ID	1/2
0300	DTM		O/1		For GISB, this segment is mandatory.		
		DTM01 - 374	M	102 - Issue		ID	3/3
		DTM05 - 1250	X	DT - Date and Time - CCYYMMDDHHMM	mark as must use	ID	2/3
		DTM06 - 1251	X	Statement Date/Time (M)	mark as must use	AN	1/35
0400	III		O/>1				
		III01 - 1270	X	VAL - Validation	mark as must use	ID	1/3
		III02 - 1271	X	Validation Code (C)	mark as must use	AN	1/30
		III04 - 933	X	Validation Message (SO)	For GISB, this element is sender's option	AN	1/264
		N1 loop	>1	(1st occurrence)			

ANSI Compliant Nomination Quick Response and Confirmation Response Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
0500	N1		M/1		For GISB, this segment should occur once for each value in the N101 element..		
		N101 - 98	M	40 - Receiver	element note: Statement Recipient ID	ID	2/3
		N103 - 66	X	1 - D-U-N-S Number	mark as must use	ID	1/2
		N104 - 67	X	Statement Recipient ID (M)	mark as must use	AN	2/17 *
		<b>N1 loop</b>	<b>&gt;1</b>	<b>(2nd occurrence)</b>			
0500	N1		M/1				
		N101 - 98	M	41 - Submitter	element note: Preparer ID [note: we are changing this from P1 because of the definition of P1]	ID	2/3
		N103 - 66	X	1 - D-U-N-S Number	mark as must use	ID	1/2
		N104 - 67	X	Preparer ID (M)	mark as must use	AN	2/17 *
<b>Detail:</b>							
		<b>N9 loop</b>	<b>&gt;1</b>				
0100	N9		O/1				
		N901 - 128	M	06 - System Number		ID	2/3
		N902 - 127	X	assigned identification	mark as must use Element note: The identifier assigned by the PDA originator in the N902.	AN	1/11 *
0600	III		O/>1				
		III01 - 1270	X	VAL - Validation	mark as must use	ID	1/3
		III02 - 1271	X	Validation Code (C)	mark as must use	AN	1/30
		III04 - 933	X	Validation Message (SO)	For GISB, this element is sender's option	AN	1/264
<b>Sub-detail:</b>							
		<b>SLN loop</b>	<b>&gt;1</b>				
0700	SLN		O/1				
		SLN01 - 350	M	PDA Submitter's Tracking ID (C)		AN	1/11 *

ANSI Compliant Nomination Quick Response and Confirmation Response Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
		SLN03 - 662	M	I - Included		ID	1/1
0900	III		O/>1				
		III01 - 1270	X	VAL - Validation	mark as must use	ID	1/3
		III02 - 1271	X	Validation Code (C)	mark as must use	AN	1/30
		III04 - 933	X	Validation Message (SO)	For GISB, this element is sender's option	AN	1/264
1600	SE		M/1				

\* GISB Min/Max column will contain an \* when the GISB values are different than the ANSI ASC X12 values

New items requested from DISA in conjunction with this document:  
none