

ANSI Compliant Nomination Quick Response Working Document

Discussed at the following meetings:

1/22/2000

mapped to ASC X12 874; used version 4032 as a base X12 standard

GISB Nomination Quick Response (1.4.2)

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
----------	---------	---------	------------------------	--	---	----------------	-----------------

Heading:

0100	ST		M/1				
0200	BGN		M/1				
		BGN01 - 353	M	27 - Verify		ID	2/2
		BGN02 - 127	M	assigned identifier	The nomination number assigned by the nomination originator in the BGN02.	AN	1/22 *
		BGN03 - 373	M	date	The nomination issue date.	DT	8/8
		BGN07 - 640	O	V2 - Natural Gas Nomination Quick Response	mark as must use	ID	2/2
		BGN08 - 306	O	Transaction Status Code (M) EZ - Exception Occurred RZ - Reject - Header Level Errors WQ - Accept	mark as must use	ID	1/2
0400	III		O/>1		For GISB, this segment is mandatory when BGN08 = 'RZ' or when BGN08 = 'EZ' and warning(s) exist at the header level.		
		III01 - 1270	X	VAL - Validation	mark as must use	ID	1/3
		III02 - 1271	X	Validation Code (C)	mark as must use	AN	1/30

ANSI Compliant Nomination Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
		III04 - 933	X	Validation Message (SO)	For GISB, this element is sender's option. However, if sending an error or warning code that has not yet been approved by GISB, but not yet published, the Validation Message should be sent for further clarification.	AN	1/80*
		N1 loop	>1	(1st occurrence)			
0500	N1		M/1		For GISB, this segment is mandatory and should occur once for each value indicated in the N101 element..		
		N101 - 98	M	78 - Service Requester		ID	2/3
		N103 - 66	X	1 - D-U-N-S Number	mark as must use	ID	1/2
		N104 - 67	X	Service Requester (M)	mark as must use	AN	2/17 *
		N1 loop	>1	(2nd occurrence)			
0500	N1		M/1				
		N101 - 98	M	SJ - Service Provider		ID	2/3
		N103 - 66	X	1 - D-U-N-S Number	mark as must use	ID	1/2
		N104 - 67	X	Transportation Service Provider (M)	mark as must use	AN	2/17 *
Detail:							
		N9 loop	>1				
0100	N9		O/1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the detail or sub-detail level.		
		N901 - 128	M	2H - Assigned by transaction set sender		ID	2/3
		N902 - 127	X		mark as must use	AN	1/50

ANSI Compliant Nomination Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
0200	DTM		O/1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the detail level.		
		DTM01 - 374	M	007 197		ID	2/3
		DTM05 - 1250	X	D8 DT	mark as must use	AN	2/3
		DTM06 - 1251	X	Beginning Date (C), Beginning Time (C), Ending Date (C), Ending Time (C)	mark as must use	AN	1/35
0400	CS		O/1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the detail level.		
		CS04 - 128	X	KSR - Service Requester Contract	Mark as must use	ID	2/3
		CS05 - 127	X	Service Requester Contract (C)	mark as must use	AN	1/30*
0600	III		O/>1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the detail level.		
		III01 - 1270	X	VAL - Validation	mark as must use	ID	1/3
		III02 - 1271	X	Validation Code (C)	mark as must use	AN	1/30

ANSI Compliant Nomination Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
		III04 - 933	X	Validation Message (SO)	For GISB, this element is sender's option. However, if sending an error or warning code that has been approved by GISB, but not yet published, the Validation Message should be sent for further clarification.	AN	1/80*
Sub-detail:							
		SLN loop	>1				
0700	SLN		O/1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the sub-detail level.		
		SLN01 - 350	M	Nominator's Tracking ID		AN	1/11 *
		SLN03 - 662	M	I - Included		ID	1/1
0800	REF		O/>1		For GISB, this segment is mutually agreed.		
		REF01 - 128	M	BE		ID	1/3
		REF02 - 1271	X	Service Provider's Activity Code (MA)	mark as must use	AN	1/30*
0900	III		O/>1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the sub-detail level.		
		III01 - 1270	X	VAL - Validation	mark as must use	ID	1/3
		III02 - 1271	X	Validation Code (C)	mark as must use	AN	1/30

ANSI Compliant Nomination Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
		III04 - 933	X	Validation Message (SO)	For GISB, this element is sender's option. However, if sending an error or warning code that has been approved by GISB, but not yet published, the Validation Message should be sent for further clarification.	AN	1/80*
1000	SE		M/1				

* GISB Min/Max column will contain an * when the GISB values are different than the ANSI ASC X12 values

New items requested from DISA in conjunction with this document:
none