

ANSI Compliant Confirmation Response Quick Response Working Document

Discussed at the following meetings:

1/25/2000

mapped to ASC X12 874; used version 4032 as a base X12 standard

GISB Confirmation Response Quick Response (1.4.7)

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
----------	---------	---------	------------------------	--	---	----------------	-----------------

Heading:

0100	ST		M/1				
0200	BGN		M/1				
		BGN01 - 353	M	27 - Verify		ID	2/2
		BGN02 - 127	M	Transaction Identifier (M)		AN	1/22 *
		BGN03 - 373	M	Date	The confirmation response quick response issue date.	DT	8/8
		BGN07 - 640	O	V3 - Confirmation Response Quick Response	mark as must use	ID	2/2
		BGN08 - 306	O	Transaction Status Code (M) EZ - Exception Occurred RZ - Reject - Header Level Errors WQ - Accept	mark as must use	ID	1/2
0400	III		O/>1		For GISB, this segment is mandatory when BGN08 = 'RZ' or when BGN08 = 'EZ' and warning(s) exist at the header level.		
		III01 - 1270	X	VAL - Validation	mark as must use	ID	1/3
		III02 - 1271	X	Validation Code (C)	mark as must use	AN	1/30

ANSI Compliant Confirmation Response Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
		III04 - 933	X	Validation Message (SO)	For GISB, this element is sender's option. However, if sending an error or warning code that has been approved by GISB, but not yet published, the Validation Message should be sent for further clarification.	AN	1/80*
		N1 loop	>1	(1st occurrence)			
0500	N1		M/1		For GISB, this segment is mandatory and should occur once for each value indicated in the N101 element..		
		N101 - 98	M	CNP - Confirming Party		ID	2/3
		N103 - 66	X	1 - D-U-N-S Number	mark as must use	ID	1/2
		N104 - 67	X	Confirming Party (M)	mark as must use	AN	2/17 *
		N1 loop	>1	(2nd occurrence)			
0500	N1		M/1				
		N101 - 98	M	CNR - Confirmation Requester		ID	2/3
		N103 - 66	X	1 - D-U-N-S Number	mark as must use	ID	1/2
		N104 - 67	X	Confirmation Requester (M)	mark as must use	AN	2/17 *
Detail:							
		N9 loop	>1				
0100	N9		O/1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the detail or sub-detail level.		
		N901 - 128	M	2H - Assigned by transaction set sender		ID	2/3
		N902 - 127	X		mark as must use	AN	1/50

ANSI Compliant Confirmation Response Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
0200	DTM		O/1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the detail level or sub-detail level.		
		DTM01 - 374	M	007		ID	2/3
		DTM05 - 1250	X	RD8, RDT	mark as must use	AN	2/3
		DTM06 - 1251	X	Beginning Date (C), Beginning Time (C), Ending Date (C), Ending Time (C)	mark as must use	AN	1/35
0300	LCD		O/1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the detail or sub-detail level.		
		LCD02 - 98	O	LCN	mark as must use	ID	2/3
		LCD05 - 66	X	DR, SV	mark as must use	ID	1/2
		LCD06 - 67	X	Location (C)	mark as must use	AN	2/17*
0400	CS		O/1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the detail or sub-detail level.		
		CS01 - 367	O	Confirmation Service Contract (C)	mark as must use	O	1/30
0500	N1		O/1		For GISB, this segment is conditional.		
		N101 - 98	M	CNS		ID	2/3
		N103 - 66	X	1	mark as must use	ID	1/2
		N104 - 67	X	Confirmation Service Identifier Code (C)	mark as must use	AN	2/17*

ANSI Compliant Confirmation Response Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
0600	III		O/>1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the detail level.		
		III01 - 1270	X	VAL - Validation	mark as must use	ID	1/3
		III02 - 1271	X	Validation Code (C)	mark as must use	AN	1/30
		III04 - 933	X	Validation Message (SO)	For GISB, this element is sender's option. However, if sending an error or warning code that has been approved by GISB, but not yet published, the Validation Message should be sent for further clarification.	AN	1/80*
Sub-detail:							
		SLN loop	>1				
0700	SLN		O/1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the sub-detail level.		
		SLN01 - 350	M	Confirmation Tracking Identifier		AN	1/11 *
		SLN03 - 662	M	I - Included		ID	1/1
0900	III		O/>1		For GISB, this segment is mandatory when BGN08 = 'EZ' and the error(s) or warning(s) exist at the sub-detail level.		
		III01 - 1270	X	VAL - Validation	mark as must use	ID	1/3
		III02 - 1271	X	Validation Code (C)	mark as must use	AN	1/30

ANSI Compliant Confirmation Response Quick Response Working Document

Position	Segment	Element	ANSI req des / max use	Literal contents or GISB data element name (and usage)	GISB segment/element note [or other comments]	ANSI data type	GISB Min/ Max *
		III04 - 933	X	Validation Message (SO)	For GISB, this element is sender's option. However, if sending an error or warning code that has been approved by GISB, but not yet published, the Validation Message should be sent for further clarification.	AN	1/80*
1000	SE		M/1				

* GISB Min/Max column will contain an * when the GISB values are different than the ANSI ASC X12 values

New items requested from DISA in conjunction with this document:
none